



HabasitLINK® M1185 Flush Grid 0.5"



Description

- Imperial belt width
- 47% open area; 84% open contact area; largest opening 8x21 mm (0.3"x0.83")
- Open hinge
- Food approved materials available
- Rod diameter 3.6 mm (0.14")
- Smart Fit rod retention
- Double row bidirectional sprocket
- Suitable for Ø 12.7 mm (0.5") nosebar



Belt data

Belt material		PP		POM		POM +DE	PA	PA +US
Rod material		PP	POM	PA	PBT	PA		
Nominal tensile strength F'_N straight run	N/m	2600	3100	4400	4250	4400	4400	4400
	lb/ft	178	212	301	291	301	301	301
Temperature range	°C	5 - 105	5 - 93	-40 - 93	-40 - 93	-40 - 93	-46 - 130	-46 - 116
	°F	40 - 220	40 - 200	-40 - 200	-40 - 200	-40 - 200	-50 - 266	-50 - 240
Temperature maximum (short-term)	°C						160	135
	°F						320	275
Belt weight m_B	kg/m ²	2.5	2.8	3.6	3.6	3.6	3.1	3.1
	lb/sqft	0.51	0.57	0.75	0.75	0.75	0.64	0.64

Diameter of idling rollers (minimum)		Diameter of support rollers (minimum)		Diameter for gravity take-up and center drive rollers (minimum)		Backbending radius for elevators without side guards or hold down devices (minimum)	
mm	inch	mm	inch	mm	inch	mm	inch
12	0.5	50	2	75	3	150	6

Diameter of idling rollers (min.): ² Minimum diameter for nosebar transfer.

Standard range of belt widths b_0

mm (nom.)	203	254	305	356	406	457	508	559	610	660	711	762	813	864	etc.
inch (nom.)	8	10	12	14	16	18	20	22	24	26	28	30	32	24	etc.

Real belt widths are in most cases 0.1% to 0.3% smaller.

For PP material up to 750 mm (30") -3 mm to 0 mm and -0.3% to 0.1% for wider belts.

For POM material up to 750 mm (30") -3 mm to 0 mm and -0.4% to 0% for wider belts.

Standard belt widths in increments of 50.8 mm (2"). Non-standard widths are offered in increments of 12.7 mm (0.5"). Smallest possible width 177.8 mm (7").

For detailed material properties refer to the HabasitLINK® Engineering Guidelines.

The nominal tensile strength is valid for 23 °C (73 °F). The admissible tensile force depends on the operating temperature near the drive sprockets. Within the temperature range allowed, the admissible tensile force may vary from 100% to 20% of the nominal tensile strength. For detailed information and correct calculation of effective

HabasitLINK®

M1185 Flush Grid 0.5"



tensile force refer to the Calculation Guide in the HabasitLINK® Engineering Guidelines.

Disclaimer

Product Application Disclaimer (valid for ALL Habasit products and mentioned on all PDS)

This disclaimer is made by and on behalf of Habasit and its affiliated companies, directors, employees, agents and contractors (hereinafter collectively "HABASIT") with respect to the products referred to herein (the "Products"). SAFETY WARNINGS SHOULD BE READ CAREFULLY AND ANY RECOMMENDED SAFETY PRECAUTIONS BE FOLLOWED STRICTLY! Please refer to the Safety Warnings herein, in the Habasit catalogue as well as installation and operating manuals. All indications / information as to the application, use and performance of the Products are recommendations provided with due diligence and care, but no representations or warranties of any kind are made as to their completeness, accuracy or suitability for a particular purpose. The data provided herein are based on laboratory application with small-scale test equipment, running at standard conditions, and do not necessarily match product performance in industrial use. New knowledge and experience may lead to re-assessments and modifications within a short period of time and without prior notice.

EXCEPT AS EXPLICITLY WARRANTED BY HABASIT, WHICH WARRANTIES ARE EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, THE PRODUCTS ARE PROVIDED "AS IS". HABASIT DISCLAIMS ALL OTHER WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT, OR ARISING FROM A COURSE OF DEALING, USAGE, OR TRADE PRACTICE, ALL OF WHICH ARE HEREBY EXCLUDED TO THE EXTENT ALLOWED BY APPLICABLE LAW. BECAUSE CONDITIONS OF USE IN INDUSTRIAL APPLICATION ARE OUTSIDE OF HABASIT'S CONTROL, HABASIT DOES NOT ASSUME ANY LIABILITY CONCERNING THE SUITABILITY AND PROCESS ABILITY OF THE PRODUCTS, INCLUDING INDICATIONS ON PROCESS RESULTS AND OUTPUT.