




### Description

- 0% open area
- Low noise accumulation rollers
- Rod diameter: 6 mm (0.22")
- Smart Fit rod retention
- Food approved materials available
- Back bending radius: 200 mm (8")
- Optimized for Low Back Pressure (LBP) accumulation
- Double row solid and split sprockets

### Available Accessories

- Tab modules with 2 tabs (Code: -T2 double tab)



### Belt data

| Belt material                   |                              | POM                   |                       |
|---------------------------------|------------------------------|-----------------------|-----------------------|
| Rod material                    |                              | PBT                   | PA                    |
| Nominal tensile strength $F'_N$ | N/m<br>lb/ft                 | 35000<br>2397         | 45000<br>3082         |
| Temperature range               | °C<br>°F                     | -40 - 93<br>-40 - 200 | -40 - 93<br>-40 - 200 |
| Belt weight $m_B$               | kg/m <sup>2</sup><br>lb/sqft | 29.3<br>6.00          | 29.3<br>6.00          |

| Diameter of idling rollers (minimum) |      |
|--------------------------------------|------|
| mm                                   | inch |
| 50                                   | 2    |

### Standard range of belt widths $b_0$

|             |      |      |       |       |       |       |       |       |       |       |       |       |       |      |
|-------------|------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|------|
| mm (nom.)   | 85   | 170  | 255   | 340   | 425   | 510   | 595   | 680   | 765   | 850   | 935   | 1020  | 1105  | etc. |
| inch (nom.) | 3.35 | 6.69 | 10.04 | 13.39 | 16.73 | 20.08 | 23.43 | 26.77 | 30.12 | 33.46 | 36.81 | 40.16 | 43.50 | etc. |

Real belt widths are in most cases 0.1% to 0.3% smaller.

For POM material up to 750 mm (30") -3 mm to 0 mm and -0.4% to 0% for wider belts.

**Standard belt widths** in increments of 85 mm (3.35"). Smallest possible width 85 mm (3.35"). Non-bricklaid belts 85 mm (3.35") and 170 mm (6.69") wide.

**For detailed material properties** refer to the HabasitLINK® Engineering Guidelines.

**The nominal tensile strength** is valid for 23 °C (73 °F). The admissible tensile force depends on the operating temperature near the drive sprockets. Within the temperature range allowed, the admissible tensile force may vary from 100% to 20% of the nominal tensile strength. For detailed information and correct calculation of effective tensile force refer to the Calculation Guide in the HabasitLINK® Engineering Guidelines.

# HabasitLINK®

## M2620 Roller Top - LBP 1"



### **Disclaimer**

#### **Product Application Disclaimer (valid for ALL Habasit products and mentioned on all PDS)**

This disclaimer is made by and on behalf of Habasit and its affiliated companies, directors, employees, agents and contractors (hereinafter collectively "HABASIT") with respect to the products referred to herein (the "Products"). SAFETY WARNINGS SHOULD BE READ CAREFULLY AND ANY RECOMMENDED SAFETY PRECAUTIONS BE FOLLOWED STRICTLY! Please refer to the Safety Warnings herein, in the Habasit catalogue as well as installation and operating manuals. All indications / information as to the application, use and performance of the Products are recommendations provided with due diligence and care, but no representations or warranties of any kind are made as to their completeness, accuracy or suitability for a particular purpose. The data provided herein are based on laboratory application with small-scale test equipment, running at standard conditions, and do not necessarily match product performance in industrial use. New knowledge and experience may lead to re-assessments and modifications within a short period of time and without prior notice.

EXCEPT AS EXPLICITLY WARRANTED BY HABASIT, WHICH WARRANTIES ARE EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, THE PRODUCTS ARE PROVIDED "AS IS". HABASIT DISCLAIMS ALL OTHER WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT, OR ARISING FROM A COURSE OF DEALING, USAGE, OR TRADE PRACTICE, ALL OF WHICH ARE HEREBY EXCLUDED TO THE EXTENT ALLOWED BY APPLICABLE LAW. BECAUSE CONDITIONS OF USE IN INDUSTRIAL APPLICATION ARE OUTSIDE OF HABASIT'S CONTROL, HABASIT DOES NOT ASSUME ANY LIABILITY CONCERNING THE SUITABILITY AND PROCESS ABILITY OF THE PRODUCTS, INCLUDING INDICATIONS ON PROCESS RESULTS AND OUTPUT.