


# HabasitLINK® M5065 Flat Top 2" HyCLEAN



## Description

- 0% open area
- Solid plate
- Imperial belt width
- Extra wide dynamic open hinge (6" link pitch)
- 85% rod exposure, superior cleanability
- Seamless up to 24" belt width
- Rod diameter 7 mm (0.27")
- Smart Fit rod retention
- Food approved materials available



## Belt data

Belt material		POM +IM			PE
Rod material		POM	PA	PBT	PE
Nominal tensile strength $F'_N$ straight run	N/m	6200	5300	4800	2400
	lb/ft	428	363	329	164
Temperature range	°C	-40 - 93	-40 - 93	-40 - 93	-70 - 65
	°F	-40 - 200	-40 - 200	-40 - 200	-94 - 150
Belt weight $m_B$	kg/m <sup>2</sup>	12.2	12.2	12.2	8.7
	lb/sqft	2.50	2.50	2.50	1.78

Belt material		PE		
Rod material		POM		
Nominal tensile strength $F'_N$ straight run	N/m	3300		
	lb/ft	226		
Temperature range	°C	-40 - 65		
	°F	-40 - 150		
Belt weight $m_B$	kg/m <sup>2</sup>	8.7		
	lb/sqft	1.78		

Diameter of idling rollers (minimum)		Diameter of support rollers (minimum)		Diameter for gravity take-up and center drive rollers (minimum)		Backbending radius for elevators without side guards or hold down devices (minimum)		Backbending radius for elevators with side guards or hold down devices (minimum)	
mm	inch	mm	inch	mm	inch	mm	inch	mm	inch
90	4	100	4	150	6	150	6	250.0	10

## Standard range of belt widths $b$ ,

mm (nom.)	152	229	305	381	457	633	610	686	762	838	914	991	1067	etc.
inch (nom.)	6	9	12	15	18	21	24	27	30	33	36	39	42	etc.

Real belt widths are in most cases 0.1% to 0.3% wider.

For PE material up to 750 mm (30") -3 mm to 0 mm and -0.4% to 0% for wider belts.

# HabasitLINK®

## M5065 Flat Top 2" HyCLEAN



**Standard belt widths** in increments of 3" (76.2 mm). Non-standard widths are offered in increments of 1.5" (38.1 mm). Smallest possible width 6.0" (152.4 mm).

Real belt widths are in most cases 0.1% to 0.3% wider.

**For detailed material properties** refer to the HabasitLINK® Engineering Guidelines.

**The nominal tensile strength** is valid for 23 °C (73 °F). The admissible tensile force depends on the operating temperature near the drive sprockets. Within the temperature range allowed, the admissible tensile force may vary from 100% to 20% of the nominal tensile strength. For detailed information and correct calculation of effective tensile force refer to the Calculation Guide in the HabasitLINK® Engineering Guidelines.

### Disclaimer

#### Product Application Disclaimer (valid for ALL Habasit products and mentioned on all PDS)

This disclaimer is made by and on behalf of Habasit and its affiliated companies, directors, employees, agents and contractors (hereinafter collectively "HABASIT") with respect to the products referred to herein (the "Products"). SAFETY WARNINGS SHOULD BE READ CAREFULLY AND ANY RECOMMENDED SAFETY PRECAUTIONS BE FOLLOWED STRICTLY! Please refer to the Safety Warnings herein, in the Habasit catalogue as well as installation and operating manuals. All indications / information as to the application, use and performance of the Products are recommendations provided with due diligence and care, but no representations or warranties of any kind are made as to their completeness, accuracy or suitability for a particular purpose. The data provided herein are based on laboratory application with small-scale test equipment, running at standard conditions, and do not necessarily match product performance in industrial use. New knowledge and experience may lead to re-assessments and modifications within a short period of time and without prior notice. EXCEPT AS EXPLICITLY WARRANTED BY HABASIT, WHICH WARRANTIES ARE EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, THE PRODUCTS ARE PROVIDED "AS IS". HABASIT DISCLAIMS ALL OTHER WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT, OR ARISING FROM A COURSE OF DEALING, USAGE, OR TRADE PRACTICE, ALL OF WHICH ARE HEREBY EXCLUDED TO THE EXTENT ALLOWED BY APPLICABLE LAW. BECAUSE CONDITIONS OF USE IN INDUSTRIAL APPLICATION ARE OUTSIDE OF HABASIT'S CONTROL, HABASIT DOES NOT ASSUME ANY LIABILITY CONCERNING THE SUITABILITY AND PROCESS ABILITY OF THE PRODUCTS, INCLUDING INDICATIONS ON PROCESS RESULTS AND OUTPUT.